

**MP 2001SP
MP 2501SP**

Digital B&W Multi Function Printer

Copier Printer Facsimile Scanner



MP 2001SP

20
ppm B/W

MP 2501SP

25
ppm B/W

MP 2001SP/MP 2501SP

MAIN SPECIFICATIONS

GENERAL

Warm-up time:	20 seconds
First output speed:	6 seconds
Continuous output speed:	20/25 pages per minute
Memory:	Standard: 1 GB Maximum: 1.5 GB
Dimensions (W x D x H):	587 x 568 x 460/558 mm
Weight:	38/44 kg
Power source:	220 - 240 V, 50/60 Hz

COPIER

Copying process:	Laser beam scanning and electro-photographic printing
Multiple copying:	Up to 999 copies
Resolution:	600 dpi
Zoom:	From 50% to 200%

PRINTER

Printer language:	Standard: PCL5e, PCL6, XPS Option: Adobe® PostScript® 3™
Print resolution:	600 x 600 dpi
Interface:	Standard: USB 2.0, SD slot, USB Host /F, Ethernet 10 base-T/100 base-TX, Ethernet 1000 Base-T Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g), Bluetooth
Network protocol:	TCP/IP (IP v4, IP v6), IPX/SPX (Option)
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2
Mac OS environments:	Macintosh OS X v10.5 or later
UNIX environments:	UNIX Sun® Solaris: 2.6, 2.7, 2.8, 2.9, 2.10 HP-UX: 10.x, 11.x, 11i v2, 11i v3 SCO OpenServer: 5.0.6, 5.0.7, 6.0 Red-Hat® Linux Enterprise: 4, 5, 6 BM® AIX: 5L v5.3, 5L v6.1, 5L v7.1 BM® System i5™ HPT
Novell® Netware® environments (Option):	v6.5
SAP® R/3® environments:	SAP® R/3®

SCANNER

Scanning speed:	Full colour: Maximum 50 originals per minute BW: Maximum 50 originals per minute
Resolution:	Maximum: 600 dpi
Original size:	A3, A4, A5, B4, B5, B6
Bundled drivers:	Network TWAIN, Scanner utility
Scan to:	E-mail, Folder, USB, SD card, SMB, FTP, URL, NCP

FAX (Option)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Resolution:	8 x 7.7 line/mm, 200 x 200 dpi 8 x 3.85 line/mm, 200 x 100 dpi
Transmission speed:	G3: 2 second(s) (200 x 100 dpi, JBIG), 3 second(s) (200 x 100 dpi, MMR)
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	2 second(s)
Memory capacity:	Standard: 4 MB

PAPER HANDLING

Recommended paper size:	Standard paper tray(s): Minimum (A5), Maximum (A3) Bypass tray: Minimum (A6), Maximum (A3)
Paper input capacity:	Maximum: 1,350/1,600 sheets
Paper output capacity:	Maximum: 350 sheets
Paper weight:	Standard paper tray(s): 60 - 105 g/m ² Bypass tray: 60 - 162 g/m ²

ECOLOGY

Power consumption:	Maximum: 1,550 W Ready mode: 113 W Sleep mode: 0.6 W TEC (Typical Electricity Consumption): 892/1,082 Wh
--------------------	---

SOFTWARE

Standard:	SmartDeviceMonitor, Web SmartDeviceMonitor®, Web Image Monitor
Optional:	GlobalScan NX, Card Authentication Package, SAP R/3 Custom Device Type

OPTIONS

Platen cover, ADF handle, ARDF, 1 x 500-sheet paper tray, 2 x 500-sheet paper tray, One-bin tray, Low cabinet, Medium cabinet, High cabinet, Hard Disk Drive, RAM, Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g), Bluetooth, VM Card, Netware, Browser unit, Counter interface, File format converter, Copy Data Security Unit, Fax Connection Unit, Fax marker, Fax option, Unicode Font Package for SAP

CONSUMABLES

Toner capacity:	Black: 9,000 prints
-----------------	---------------------

For availability of models, options and software, please consult your local Gestetner supplier.



ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2012 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

www.gestetner.com

Gestetner